

iData 80 Extra-large screen Rugged Mobile Computer

Redefining the large screen PDAs



- **Industry pioneer large 5.7-inch screen, 18:9 full view display leading design**
 - ◆ **Large 5.7-inch screen:** big and brand new display shows more comprehensive, let you have a better view and work experience;
 - ◆ **The leading 18:9 full view display:** same vision as PAD and great handheld experience as a PDA.
- **Multiple field enterprise data collection function**
 - ◆ **Compatible with multiple types of industrial-level scanning engines,** satisfy the bar code scanning demands of different scenes;
 - ◆ **Support multiple professional data automatic recognition and collection modes like NFC, GPS and cameras,** help the users to collect the business data accurately and rapidly.
- **Enterprise-class configuration, stronger performance**
 - ◆ **Qualcomm Octa-core CPU & 2GB RAM,** with the higher performance and lower power consumption;
 - ◆ **Android OS, further optimize the iData 80,** help you cope with the multiple-task processing in a high speed and bring the more excellent smooth operation;
 - ◆ **4000mAh high-capacity battery + iData systematic-level electricity-saving optimization.**
- **Safer and more reliable**
 - ◆ iData 80 boasts an **ultra-fast fingerprint sensor** so you can swift unlock the mobile computer; supports multiple fingerprint recognition applications, satisfy all mobile application demands of Enterprises

- ♦ iData 80 can meet a protection grade of IP65 bear 1.5-meter-high drop, adapt to more complex and severe working environment.

➤ iData Series Enterprise Applications

- ♦ **iData self-developed Enterprise apps (iSeries Apps)**, among many others, it includes the iLauncher (Kiosk or Lock-down mode) where admin can customize which apps and features are available for the users of the iData 80.

System Configuration

CPU	Octa-core 1.4 GHz
Operating System	Android 7.1
Memory	16 GB ROM+2 GB RAM
Expansion Slot	Micro SD card, up to 32 GB
Display	5.7-inch, 1440 x 720 High resolution (18:9 full view display)
Touch Panel	Industrial-grade capacitive touch panel
Camera (optional)	13 MXP autofocus camera in the back side, autofocus lens, LED flash
Exit Window	Corning® Gorilla® glass
Keypad	3 front keys, 4 side keys, power key
Battery	3.8 V 4000 mAh rechargeable lithium polymer battery
Audio	Built-in microphone /Type-C USB
Notification	Vibrator alerts/LED/Audio notification
Vibration Motor	Built-in programmable vibration motor
Fingerprint module	Capacitive fingerprint module

Structural Parameters

Dimensions (LxWxD)	164 mm x 79 mm x 15.5 mm (max thickness 22mm)
Weight	240g (battery included)

Communication Transmission

Wireless WAN (Network frequency)	Asia & Europe : 2G: B2/B3/B5/B8 3G: WCDMA: B1/B2/B5/B8 CDMA&EVDO: BC0 TD-SCDMA:B34/B39 4G: FDD-LTE: B1/B3/B5/B7/B8/B20 TDD-LTE: B38/B39/B40/B41 America : 2G: B2/B3/B5/B8 3G: B2/B5/B8
-------------------------------------	---

	4G: B2/B4/B5/B13/B17
Wireless WAN (Data service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/EVDO/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless LAN	Wi-Fi 802.11 a/b/g/n/ac (Dual-band Wi-Fi: 2.4G+5G)
Bluetooth	Bluetooth 4.1
GPS	Supporting GPS/AGPS/Glonass/Beidou Compass

Operating Environment

Development Tools	Android SDK+ JDK+Eclipse
Programming Language	Java
Operating Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Storage Temp.	-40°C ~ 60°C (-40°F ~140°F) battery included -40°C ~ 70°C (-40°F ~158°F) battery not included
Relative Humidity	0 ~ 95% (non-condensing)
Drop Specification	1.5-meter drops to concrete ground
Sealing	IP65
Electrostatic Discharge	Conforms to ±15 kV air discharge, ±8 kV direct discharge

2D Area Imager

Scan Precision	3mil c39/128
Rotate Angle	360°
Pitch Angle	±45°
Skew Tolerance	±65°
Scan Frequency	1 scans /50ms
Laser Safety Grade	Class II
Image Resolution	844(H)×640(V)
Image Frame	60fps
Light Source System	White light, laser aiming
Minimum Printing Contrast	20%
Code Support	Aztec Code , Codabar , Codablock F , Code 11 , Code 128 , Code 2 of 5 , Code 39 , Code 93 , Data Matrix , EAN/JAN-13 , EAN/JAN 8 , EAN-UCC Composite Codes , EAN-UCC Emulation , IATA Code 2 of 5 , Interleaved 2 of 5 , Matrix 2 of 5 , MaxiCode , MicroPDF417 , MSI , PDF417 , Postal Codes (Australian Post , British Post , Canadian Post , China Post , Japanese Post , Korea Post ,

	Netherlands Post , Planet Code , Postnet) , Plessey Code , PosiCode , QR Code , RSS Expanded , RSS Limited, RSS-14 , TCIF Linked Code 39 , Telepen , Trioptic Code , UPC-A , UPC-E, etc.
--	---

NFC

Frequency	13.56 MHz
Reading Distance	Within 30 mm
Protocol	ISO14443A/14443B/15693

Input / Output Ports

USB Port	1 (Type-C USB port)
Charger Port	1

Accessories

Standard	Battery, Power adapter, Hand strap
Optional	USB cable, Single cradle, 4-slot device cradle, Carry case, Waist bag



IDATA GLOBAL

Commercial HQ: Rm. 502, Sci.&Tech. Park Building, No.6, Keyuan Road,
Science and Technology Park, Shenzhen City, China

E-mail: sales@idataglobal.com

Website: www.idataglobal.com