



# XP-DT427B

## Thermal Label Printer

### (USB, Bluetooth & Ethernet)

The XP-DT427B is your reliable solution for efficient and high-quality label printing. This compact and user-friendly printer is perfect for a wide range of applications, from retail and logistics to healthcare and more.

Built with durability in mind, the XP-DT427B is crafted from high-quality materials, ensuring a long lifespan and consistent performance. This printer is designed to withstand the rigors of daily use, making it a reliable asset for your business.

#### Multiple Connectivity Options

Equipped with USB, Bluetooth and Ethernet interfaces, the XP-DT427B ensures seamless integration with various systems and platforms. Print from desktops, laptops, tablets, or mobile devices with minimal setup.

#### User-Friendly Interface

Featuring an intuitive interface, the XP-DT427B is easy to set up and operate. The user-friendly design streamlines the printing process, allowing you to focus on what matters most – growing your business.



#### High-Speed Printing

Boost your productivity with the XP-DT427B's rapid printing capabilities. This thermal label printer ensures swift and accurate printing, making it ideal for busy environments where time is of the essence.

#### Wide Media Compatibility

With versatile compatibility, this printer supports various label sizes, accommodating your diverse printing needs. Whether you require shipping labels, barcodes, or product tags, the XP-DT427B has got you covered.



## Specifications

### PRINTING

Printing Method	Direct Thermal
Resolution	203 DPI
Print Speed	152mm (6 ") / per second
Max. Print Width	108mm (4.25")
Max. Print Length	1778mm (70")

### MEDIA

Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	25.4mm ~ 115mm
Media Thickness	0.06mm ~ 0.525mm (2.36" ~ 9.8")
Media Core Diameter	25.4mm ~ 76.2mm (1" ~ 3")
Label Length	10mm ~ 1778mm (0.39" ~ 90")
Label Roll Capacity	127 mm (5") OD (external diameter)



### PERFORMANCE

Processor	32-bit CPU
Memory	8MB Flash Memory   8MB SDRAM   Flash memory can expanded up to 4GB
Interface	Windows OS: USB, WIFI & Bluetooth Mac OS: USB & WIFI iOS & Android: WIFI & Bluetooth
Sensors	Gap Sensor   Cover Opening Sensor   Black Mark Sensor

### HARDWARE

Dimension	210.8mm (W) × 190.2mm (H) × 180.2mm (D)
Weight	1.40kg
Driver	Windows   Linux   Mac
SDK	Windows   iOS   Android
Power	Input: AC 100-240V Output: DC 24V / 2.5A
Environmental	5° to 40° (Operating)   -40° to 60°, 10° to 90° (Storage)



Singapore (HQ)  
All ID Asia Pte Ltd  
+65-6778-0075  
hello@allid.com.sg  
www.allid.com.sg

Malaysia  
All ID Asia Sdn Bhd  
+603-8075-1888  
hello@allid.com.my  
www.allid.com.my

Indonesia  
PT All ID Indonesia  
+62 21-4517-330  
hello@allid.co.id  
www.allid.co.id

Philippines  
All ID Philippines Inc.  
+632 224 2042  
hello@allid.com.ph  
www.allid.com.ph

Myanmar  
All ID Myanmar  
+959-777499949  
hello@allid.com.mm  
www.allid.com.mm